


Casquillos de agujas BAM1210-IKO - BAM1210-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam1210-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
19.050 (3/4)	---	---	---	---	---	---	---	---	---	---	---	---	---
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	
F_w	D	C	B	Shaft dia. h6	Housing bore dia. J7	C	C_0	C	C_0	N	N	N	Assembled inner ring
19.050	25.400	15.881 (625)	1.3	Max. 19.050	Max. 19.037	25.412	25.391	9 500	13 200	20 000	IRB #10-1		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952173009
Diámetro interior	19.05 mm
Diámetro exterior	25.4 mm
Espesor	15.88 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE