

Casquillos de agujas BAM1418-IKO - BAM1418-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam1418-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 (7/8)	—	—	—	—	—	—	—	BAM 1418	37	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	Shaft dia. h_6		Housing bore dia. J_7		C	C_0	rpm	—	
mm	mm	mm	Max.	Min.	Max.	Min.	N	N			
22.225	28.575	28.581.125	2.8	22.225	22.212	28.587	28.566	19 900	35 600	18 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952173160
Diámetro interior	22.23 mm
Diámetro exterior	28.58 mm
Espesor	28.58 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE