


Casquillos de agujas BAM1422-IKO - BAM1422-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam1422-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g																																																	
	Standard	Mass (Ref.) g	Closed end																																																											
22.225 (7/8)	---	---	---	---	---	---	---	---	---	---	---	---	---																																																	
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="4">Standard mounting dimensions</th> <th colspan="2">Basic dynamic load rating</th> <th colspan="2">Basic static load rating</th> <th colspan="1">Allowable rotational speed⁽¹⁾</th> <th colspan="1">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th colspan="2">Shaft dia. h6</th> <th colspan="2">Housing bore dia. J7</th> <th>C</th> <th>C_0</th> <th>C_0</th> <th>rpm</th> <th></th> </tr> <tr> <td></td> <td></td> <td></td> <td>Max.</td> <td>Min.</td> <td>Max.</td> <td>Min.</td> <td>N</td> <td>N</td> <td>N</td> <td></td> <td></td> </tr> </thead> <tbody> <tr> <td>22.225</td> <td>28.575</td> <td>34.92(1.375)</td> <td>2.8</td> <td>22.225</td> <td>22.212</td> <td>28.587</td> <td>28.566</td> <td>24 100</td> <td>45 700</td> <td>18 000</td> <td>IRB 1022</td> </tr> </tbody> </table>														Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring	F_w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C_0	C_0	rpm					Max.	Min.	Max.	Min.	N	N	N			22.225	28.575	34.92(1.375)	2.8	22.225	22.212	28.587	28.566	24 100	45 700	18 000	IRB 1022
Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring																																																		
F_w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C_0	C_0	rpm																																																				
			Max.	Min.	Max.	Min.	N	N	N																																																					
22.225	28.575	34.92(1.375)	2.8	22.225	22.212	28.587	28.566	24 100	45 700	18 000	IRB 1022																																																			

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952173177
Diámetro interior	22.23 mm
Diámetro exterior	28.58 mm
Espesor	34.92 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE