


Casquillos de agujas BAM1510-IKO - BAM1510-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam1510-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
23.812 ($\frac{9}{4}$)	—	—	—	—	—	—	—	BAM 1510	23	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring		
F_w	D	C	f_s	Shaft dia. mm	Housing bore dia. mm	C	C_0	rpm			
23.812 $\frac{9}{4}$	30.162 $1\frac{1}{8}$	15.88 $\frac{5}{8}$	2.8	23.812 23.799	30.176 30.151	11 000	17 100	16 000	IRB 1110		

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952173207
Diámetro interior	23.81 mm
Diámetro exterior	30.16 mm
Espesor	15.88 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE