

Casquillos de agujas BAM1516-IKO - BAM1516-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam1516-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
23.812 ($\frac{9}{16}$)	---	---	---	---	---	---	---	---	---	---	---	---	---
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring						
F _w	D	C	Shaft dia. h ₈ Max. Min.					Housing bore dia. j7 Max. Min.					
23.812 $\frac{9}{16}$	30.162 $1\frac{1}{8}$	25.40 1.000	2.8	23.812 23.799	30.176 30.151	18 900	34 300	16 000	IRB 1116				

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952173214
Diámetro interior	23.81 mm
Diámetro interior	15/16" inch
Diámetro exterior	30.16 mm
Diámetro exterior	1 3/16" inch
Espesor	25.4 mm
Espesor	1" inch
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE