

Casquillos de agujas BAM168-IKO - BAM168-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam168-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number			Identification number			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end				
25.400 (1)	---	---	---	---	---	---	BAM 168	20.5	---	---
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Shaft dia. mm		Housing bore dia. mm		Assembled inner ring
F _w	D	C	t	Shaft dia. mm Max. Min.	Housing bore dia. mm Max. Min.	J7	N	N	15 000	
25.400	31.750	12.70	2.8	25.400 25.387	31.764 31.739	J7	8 240	12 000	15 000	IRB 128

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952173306
Diámetro interior	25.4 mm
Diámetro exterior	31.75 mm
Espesor	12.7 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE