

Casquillos de agujas BAM188-IKO - BAM188-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam188-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring		
	Standard	Mass (Ref.) g	Closed end Mass (Ref.) g						
28.575 (1 1/8)	---	---	---	BAM 188	23	---	---		
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Shaft dia. h8 Max. Min.	Housing bore dia. J7 Max. Min.	Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring
F _w	D	C	t						
28.575 1 1/8	34.925 1 3/8	12.70 500	2.8	28.575 28.562	34.939 34.914	8 680	13 400	13 000	IRB 148

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952173375
Diámetro interior	28.58 mm
Diámetro exterior	34.93 mm
Espesor	12.7 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE