



Casquillos de agujas BAM1910-IKO - BAM1910-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam1910-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g					
	Standard	Mass (Ref.) g	Closed end															
30.162 (1 1/8)	---	---	---	---	---	---	---	---	---	---	---	---	---					
Boundary dimensions mm(inch)																		
F _w			D			C			Shaft dia. mm			Housing bore dia. mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed(*) rpm	Assembled inner ring
Max.			Min.			Max.			Min.			N	N					
30.162 (1 1/8)			38.100 (1 1/2)			15.88 (.625)			30.162 (30.146)			38.114 (38.089)			15 000	22 500	12 000	---

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952173382
Diámetro interior	30.16 mm
Diámetro exterior	38.1 mm
Espesor	15.88 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE