


Casquillos de agujas BAM56-IKO - BAM56-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam56-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
7.938 ($\frac{5}{16}$)	—	—	—	—	—	—	—	BAM 56	3.9	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring		
F_w	D	C	h_2 Max.	Shaft dia. h_8 Max. Min.	Housing bore dia. J_7 Max. Min.	C	C_0	rpm			
7.938	12.700	9.521	3.75	1	7.938 7.929 12.710 12.692	2 620	2 390	45 000	—		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952173443
Diámetro interior	7.94 mm
Diámetro exterior	12.7 mm
Espesor	9.52 mm
Peso	3.9 g
Envasado	-
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE