

Casquillos de agujas
BAM77-IKO - BAM77-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam77-iko>



SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
11.112 (.437)	—	—	—	—	—	—	—	—	—	—	—	—	—
Boundary dimensions mm (inch) Standard mounting dimensions mm													
F_w	D	C	b_2	Shaft dia. h8	Housing bore dia. J7	Basic dynamic load rating C	Basic static load rating C0	Allowable rotational speed ⁽¹⁾	Assembled inner ring				
11.112 (.437)	15.875 (.625)	11.13 (.438)	1	11.112 Max.	11.101 Min.	15.885 Max.	15.867 Min.	4 150 N	4 680 N	35 000 rpm	—		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952173542
Diámetro interior	11.11 mm
Diámetro exterior	15.88 mm
Espesor	11.13 mm
Envasado	1

contacto@123rodamiento.es
911 436 830
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE