


## Rodamiento conico 2474-2420-TIMKEN - 2474-2420-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/2474-2420-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
28.575	68.262	22.225	6768	1.17	17500	16200	1.72	23200	2474	
1.1250	2.6875	0.8750	15500		3940	2200		16500	2420	

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage		Geometry Factors			kg					
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>		G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm						
22.812	17.462	-4.6	0.8	35.0	36.8	1.5	63.0	60.0	0.9	0.3	10.0	10.5	0.062	0.42
0.9015	0.6875	-0.26	0.03	1.38	1.42	0.06	2.48	2.38	0.03	0.01				0.90

### CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952307015
Diámetro interior	28.58 mm
Diámetro interior	1 1/8" inch
Diámetro exterior	68.26 mm
Diámetro exterior	2 11/16" inch
Espesor	22.23 mm
Espesor	7/8" inch
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE