


## Rodamiento conico 346-332A-TIMKEN - 346-332A-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/346-332a-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |        |         | Load Ratings                          |                         |                                       |                                       |                       | Part Number |       |
|--------------------|--------|---------|---------------------------------------|-------------------------|---------------------------------------|---------------------------------------|-----------------------|-------------|-------|
| Bore d             | O.D. D | Width B | Dynamic <sup>(1)</sup> C <sub>1</sub> | Factor <sup>(2)</sup> e | Dynamic <sup>(1)</sup> C <sub>2</sub> | Factor <sup>(2)</sup> C <sub>2e</sub> | Static C <sub>3</sub> | Inner       | Outer |
| mm                 | mm     | mm      | N                                     |                         | N                                     | N                                     | N                     |             |       |
| 31.750             | 80.000 | 24.175  | 94300                                 | 0.27                    | 24600                                 | 11400                                 | 2.14                  | E3400       | 346   |
| 1.2500             | 3.1496 | 0.9518  | 21500                                 |                         | 5480                                  | 2570                                  |                       | 18700       | 332A  |

| Bearing Dimensions |        |         |      |       |      |         |      |      |      | Geometry Factors |                |                | Bearing Weight |      |
|--------------------|--------|---------|------|-------|------|---------|------|------|------|------------------|----------------|----------------|----------------|------|
| Width B            |        | ER. Dr. |      | Shaft |      | Housing |      | Cage |      | G <sub>1</sub>   | G <sub>2</sub> | C <sub>3</sub> |                |      |
| mm                 | mm     | mm      | mm   | mm    | mm   | mm      | mm   | mm   | mm   |                  |                |                |                |      |
| 22.483             | 21.900 | -4.4    | 0.8  | 35.5  | 40.8 | 2.3     | 35.9 | 71.8 | 8.7  | 1.1              | 25.5           | 13.0           | 0.9676         | 8.89 |
| 0.8823             | 0.8328 | -0.25   | 0.03 | 1.36  | 1.57 | 0.09    | 2.95 | 2.80 | 0.32 | 0.05             |                |                |                | 1.31 |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | TIMKEN        |
| Nº Ean13          | 3663952308968 |
| Diámetro interior | 31.75 mm      |
| Diámetro exterior | 80 mm         |
| Espesor           | 24.18 mm      |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE